



# Reboot your engine

with  
**PREMIUM  
LUBRICANTS**



**Amberöl<sup>+</sup>**  
LUBRICANTS

## 4T ENGINE OIL



### ACTION FULLY-SYNTH 4T 5W-30, API SN

**Application:** ACTION FULLY-SYNTH 4T 5W-30 API SN has an anti-oxidant chemistry that is able to prevent increase in oil and engine temperature especially in air cool designs; this ensures smooth clutch operation and superb pick up giving the rider an expected performance.

**Meets Performance Level –** API SN, JASO MA2

**Recommended For :** Honda, Suzuki, Yamaha and Suitable for all BS6 Two Wheeler

**Pack Size** 600ML, 900ML, 1L, 50L, 210L



### TITANIC FULLY-SYNTH 4T 10W-40, API SN

**Application:** TITANIC FULLY-SYNTH 4T 10W-40 API SN has an anti-oxidant chemistry that is able to prevent increase in oil and engine temperature especially in air cool designs; this ensures smooth clutch operation and superb pick up giving the rider an expected performance.

**Meets Performance Level –** API SN, JASO MA2

**Recommended for:** Suzuki, Mahindra, TVS Two Wheeler & Yamaha etc.

**Pack Size** 1L, 50L, 210L.



### TITANIC FULLY-SYNTH 15W-50, API SN

**Application:** TITANIC FULLY-SYNTH 4T 15W-50 API SN provides premium performance and maximum protection in high performance. it is engineered from advanced technology to better withstand the elevated rpm, high temperatures and shock loading common to extreme applications.

**Meets Performance Level:** API SN, JASO MA2

**Recommended for:** All BS6 Engines Two Wheeler in Royal Enfield, Harley Davidson, Yamaha, Honda & Kawasaki etc.

**Pack Size** 2.5L, 50L, 210L.



### TITANIC FULLY-SYNTH 4T 20W-40, API SN

**Application:** TITANIC SYNTH 4T 20W-40 API SN has an anti-oxidant chemistry that is able to prevent increase in oil and engine temperature especially in air cool designs; this ensures smooth clutch operation and superb pick up giving the rider an expected performance.

**Meets Performance Level –** API SN, JASO MA2

**Recommended for:** Discover, TVS Apache, Hero, Splendor, Passion, Honda Shine and all other higher CC bikes available in Indian Market.

**Pack Size** 900ML, 1L, 50L, 210L.



### SUPER 4T SYNTHETIC BLEND 10W-30, SN/JASO MB

**Applications:** SUPER 4T SYNTHETIC BLEND 10W-30 API SN Recommended for new generation 4-stroke gasoline engines in high performance motorcycles with exceptional demand for fuel economy

**Meets Performance Level –** API SN, JASO MA2 / MB

**Features & Benefits:**

- MB: Recommended for all new generation Gearless Scooters

**Recommended For :** Hero, Honda, TVS, Suzuki, Bajaj, YAMAHA and all BS6 Two Wheeler ; Hero, Honda, TVS, Suzuki, Bajaj, YAMAHA and all BS6 Gearless Scooters

**Pack Size** 800ML, 900ML, 1L, 50L, 210L.



### RACE 4T SYNTHETIC BLEND 20W-40, API SN

**Application:** RACE 4T SYNTHETIC BLEND SAE 20W-40 API SN has an anti-oxidant chemistry that is able to prevent increase in oil and engine temperature especially in air cool designs; this ensures smooth clutch operation and superb pick up giving the rider an expected performance & Long drain period.

**Meets Performance Level –** API SN, JASO MA2

**Recommended for:** Discover, Hero Splendor, Passion, Honda Shine, TVS Apache and all BS6 Two Wheeler.

**Pack Size** 900ML, 1L, 50L, 210L.



### POWER 4T SYNTHETIC BLEND 20W-50, API SN

**Application:** POWER 4T SYNTHETIC BLEND SAE 20W-50 API SN has an anti-oxidant chemistry that is able to prevent increase in oil and engine temperature especially in air cool designs; this ensures smooth clutch operation and superb pick up giving the rider an expected performance & Long drain period.

**Meets Performance Level –** API SN, JASO MA2

**Recommended for:**

- All 4 Stroke 2 wheelers manufactured by Hero Moto Corp, Bajaj Auto, Pulsar, Bajaj Avenger, TVS, Yamaha, Honda, Enfield etc.
- All other highpower bikes available in India.

**Pack Size** 1L, 50L, 210L.



### KICK 2T API TC, JASO FB

KICK 2T is a 2-stroke motorcycle oil made using mineral oil base. It's increased performance provides standard engines with Protection, Exhaust emissions and soot deposits are efficiently controlled.

**Applications:** All types of 2-stroke motorcycles, scooters and mopeds. Its composition is perfectly compatible with lead free fuels. It is prediluted and therefore needs to be dosed to the manufacturer's recommendations.

- Benefits:** Combustion control • Reduction in exhaust smoke • Avoids sparks plug fouling • Less exhaust smoke at start-up

**Pack Size** 500ML, 1L, 210L.



### POWER 4T 20W-50, API SL

**Application:** POWER 4T 20W-50 All four stroke engine oil using Group II Plus base oils and high detergent & despesent additives technology to keep the engine clean. This oil is designed for use over a varied temperature range and good engine lubrication.

**Meets Performance Level:** API SL, JASO MA2

**Recommended for:**

- All types of four Stroke two wheelers manufactured by Hero Moto Corp, Bajaj Auto, TVS, Yamaha, Honda, Enfield etc.
- All other high power bikes available in India.

**Pack Size** 1 L, 1.2 L, 50 L, 210 L



### PREMIUM 4T 20W-40, API SL

**Application:** PREMIUM 4T SAE 20W-40 API SL has an anti-oxidant chemistry that is able to prevent increase in oil and engine temperature especially in air cool designs; this ensures smooth clutch operation and superb pick up giving the rider an expected performance & Long drain period.

**Meets Performance Level –** API SL, JASO MA2

**Recommended for:**

- Hero, Honda, TVS, Suzuki, Bajaj and other all Two Wheeler.

**Pack Size** 900 ML ,1L, 50L, 210L.



### SUPER 4T 10W-30 API SL

SUPER 4T 10W-30, API SL is specially formulated Premium Oil for new generation four stroke motorcycles

**Technology Advantages:**

- Formulated with premium Group II Base Oil
- Highest level of Engine, Clutch and Gear Performance
- Longer Drain Interval
- Better low temperature performance

**Recommended For :** Hero, Honda, TVS, Suzuki, Bajaj and other all Two Wheeler. Specifications: Meets JASO T 903: 2011 MA-2 spec.

**Pack Size** 800ML, 900 ML ,1L, 50L, 210L.



### FORK OIL

FRONT FORK OIL is a special product dedicated to hydraulic front fork for motorcycles.

**Features:**

- Excellent chemical stability
- Excellent seal compatibility
- Optimum damping performance in all motorcycle suspensions
- Low pour point

**Application:** It is applied to all kind of motorcycle front forks working under severe conditions.

Pack Size 175 ML, 350 ML



### CHAIN CLEANER

Amberol chain cleaner is designed to provide superior cleaning to chain linkages and roller parts. It protects from rust and corrosion. Hence, reduces wear, tear and friction. It is safe to use on chain with rubber O rings.

Pack Size 120 ML



### CHAIN LUBE

Amberol Chain Lube is specially designed to provide superior penetration and long lasting lubrication to chain linkages & roller parts. It creates a lubricant film and protects from rust and corrosion. Hence, reduces wear, tear and friction. It is safe to use on chain with rubber.

Pack Size 120 ML

## PASSANGER CAR MOTOR OIL



### TITANIC FULLY-SYNTH XP 0W-20, API SN

TITANIC SYNTH 0W-20 API SN/CF is formulated with specially selected base oils for direct injection engines, both aspirated and turbo-charged. It is a multi-grade engine oil specifically engineered to respond to all requirements of latest generations diesel engines (common-rail) and VGT petrol engines of cars

**Features & Benefits:**

- Increases Fuel Efficiency
- Improves Engine Life
- Improves Wear Reduction
- Thermal Stability Preventing oxidation

**Recommended For:** Maruti Suzuki, Hyundai, Skoda, Audi, Volkswagen, BMW, Mercedes, Honda, Maruti Super Carry and all new generation cars.

Pack Size 1L, 3L, 3.5L, 5L, 210L



### TITANIC FULLY-SYNTH GX 10W-40, API SN / CJ-4

Recommended for all applications where 10W-40 engine oil of API SN / CJ-4 is specified. Also, it is perfectly adapted to all vehicles equipped with catalyst using unleaded fuel.

**FEATURES & BENEFITS**

- Helps to maintain the life of the emission control systems as required for regulatory compliance
- Can expect less oil consumption and reduced engine wear

**MEETS OEM LEVEL PERFORMANCE:** ACEA A3/B4-04, Daimler Chrysler MB 229.3, Volkswagen VW 502.00 505.00, API: CJ-4, CI-4+, CI-4, CH-4, CG-4, CF-4/SN Er European and OEM claims. Meets or exceeds Caterpillar: ECF-2, ECF-3; Cummins: CES 20077, 81; DDC: 93K218; Deutz: DGC-III; MACK: E0-0 PP; MAN: 3275; MB Approval: 228.3, 228.31; MTU: Category 2; Volvo: VDS-4, VDS-3,

Pack Size 3.5L, 210L



### TITANIC FULLY-SYNTH XT 5W-40, API SN

TITANIC FULLY-SYNTH XT 5W-40 API SN/CF is formulated with specially selected base oils for direct injection engines, both aspirated and turbo-charged. It is a multi-grade engine oil specifically engineered to respond to all requirements of latest generations diesel engines (common-rail) and VGT petrol engines of cars

**MEETS OEM LEVEL PERFORMANCE:** ACEA A3/B4-04, Daimler Chrysler MB 229.3 Volkswagen VW 502.00 505.00

**Recommended For:** Maruti Suzuki, Hyundai, Skoda, Toyota, Audi, Volkswagen, BMW, Mercedes etc.

Pack Size 1L, 3.5L, 4L, 210LTR



### TITANIC FULLY-SYNTH ZX 5W-30, API SN

TITANIC FULLY-SYNTH ZX 5W-30 API SN/CF is formulated with specially selected base oils for direct injection engines, both aspirated and turbo-charged. It is a multi-grade engine oil specifically engineered to respond to all requirements of latest generations diesel engines (common-rail) and VGT petrol engines of cars

**MEETS OEM LEVEL PERFORMANCE:** ACEA A3/B4-04, Daimler Chrysler MB 229.3 Volkswagen VW 502.00 505.00

**Recommended For:** Maruti Suzuki, Hyundai, Skoda, Toyota, Audi, Volkswagen, BMW, Mercedes etc.

Pack Size 1L, 3.5L, 5L, 50L, 210L



### TITANIC SYNTH GT SYNTHETIC BLEND 5W-30, API SN

TITANIC SEMI-SYNTH GT 5W-30 API SN is formulated with specially selected base oils for direct injection engines, both aspirated and turbo-charged. It is a multi-grade engine oil specifically engineered to respond to all requirements of latest generations diesel engines (common-rail) and VGT petrol engines of cars

**MEETS OEM LEVEL PERFORMANCE:** ACEA A3/B4-04, Daimler Chrysler MB 229.3 Volkswagen VW 502.00 505.00

**RECOMMENDED FOR:** Maruti Suzuki, Hyundai, Tata and Toyota

Pack Size 1L, 3.5L, 5L, 50L, 210L



### TITANIC FULLY-SYNTH 20W-50 SN

TITANIC FULLY SYNTH 20W-50, API SN is premium high performance multi-grade oils for passenger cars, designed to exceed recent engine lubrication requirements for high mileage cars.

**Applications:** This product is developed for gasoline passenger car engines. This oil is suitable for a wide range of applications (city traffic, road, motorways), and in all seasons. These lubricants exceed the latest API specifications and are fully backward compatible. It can service a very wide number of engines in maintenance operations.

**Recommended For:** Maruti Suzuki and suitable for Petrol engine vehicles.

Pack Size 1L, 3L, 3.5L, 50L, 210L



### CNG & LPG 20W-50, API SL/CF

CNG & LPG 20W-50, API SL/CF is a high performance gas engine oil. Developed for vehicles running on CNG & LPG fuels. Blended with a special additive chemistry, which provides excellent protection to engines against wear, deposits and provides outstanding engine cleanliness.

**Applications:** CNG & LPG 20W-50 is formulated with advanced Green & Clean Chemistry.

**Recommended for:** Maruti Suzuki and suitable for all CNG and LPG Cars and Four stroke Engines.

Pack Size 500ML, 1L, 3L, 50L, 210L

## COOLANT

### COOL GUARD COOLANT

**Recommended for:** Use in petrol, diesel, LPG & CNG engines used in cars, trucks, tractors and generators

**Benefits:**

- Excellent corrosion protection of entire cooling system containing multi-metal components of aluminium, cast iron, brass and other metals
- Prevents scale formation and hence radiator blockage
- Dilute with 5 parts of drinking water for best cooling efficiency
- Compatible for high pressure turbocharger fitted engines
- Compatible to rubber and plastic components of cooling circuit
- Foam and fungus free • Recommended to change after 60,000 km of use



Pack Size 500ML, 1L, 3L, 5L, 210L

## DIESEL ENGINE OIL



### ULTRA TURBO PLUS 15W-40, CI-4 PLUS

ULTRA TURBO PLUS 15W-40, API CI-4 PLUS is high performance heavy duty engine oil specifically developed for low emission vehicle to extend engine life in the most severe duty on and duty on and off highway application. It meets the latest performance requirements of major vehicle manufacturer.

**Benefits:**

- Long drain interval of 80 000 km\*
- Complies to Euro IV emission norms.
- High level efficiency

**MEETS OEM LEVEL PERFORMANCE:** Volvo VDS-3, Cummins CES 20078, Daimler MB 228.3, MAN M 3275

Pack Size 1L, 3L, 5L, 6L, 7L, 7.5L, 8.5L, 10L, 15L, 16L, 20L, 50L, 210L



### ULTRA TURBO 15W-40, CH-4

ULTRA TURBO CH-4 SAE 15W-40 API CH-4 exceeds the requirements of API CH-4 and hence is able to promise extra oil life value to commercial vehicle engines fitted with turbochargers, especially for 16 to 40 tonne trucks; superior cleanliness properties ensure extra life for engine components.

- Benefits :**
- Long Drain interval of 40 000 km\*
  - Clean piston groove and valve seats

**Meets OEM Level Performance:** Daimler MB 228.3, Cummins CES 20078, Volvo VDS-3, MAN M 3275

Pack Size 500ML, 1L, 3L, 3.5L, 5L, 7.5L, 10L, 15L, 26L, 50L, 210L.



### PREMIUM TURBO 15W-40, CF-4

PREMIUM TURBO SAE 15W-40, API CF4 is a high performance multi-grade diesel engine oil. It is manufactured from high quality base oils and advanced additive technology for superior protection by reducing friction between moving parts and corrosion.

**Applications:** Recommended for use in all diesel engine Trucks – Tata Motors, Ashok Leyland, Eicher/LCVs – Swaraj Mazda, IVECO/Tractors – New Holland, John Deere, Sonalika, Mahindra, TAFE, Escorts, IITL, PTL Utility Vehicles – Tata Motors, Mahindra etc.

**Performance Level:** API CF-4, MIL-L-2104E, BIS EDL-3, Cummins CES 20075

Pack Size 500ML, 1L, 3L, 3.5L, 5L, 7.5L, 10L, 15L, 50L, 210L.



### ULTRA POWER 20W-40, CF-4

ULTRA POWER CF-4 SAE 20W-40 is a high performance multi-grade diesel engine oils specially designed for use in heavy duty, high-revolution diesel engines for on-highway and off-highway applications.

**Applications:** Recommended for use in severe duty four stroke naturally aspirated diesel engines both on-highway and off-highway.

**Benefits:**

- Excellent dispersancy, minimize soot induced oil thickening and associated engine wear.
- Prevention of low temperature sludge formation.

Pack Size 500ML, 1L, 3.5L, 5L, 7.5L, 10L, 20L, 26L, 50L, 210L



### ULTRA PREMIUM 20W-40, SC/CC

ULTRA PREMIUM 20W-40, API SC/CC Multigrade Oil is blended from highly refined base stocks and balanced additive package containing shear stable VI improver, metallic detergent dispersant and antioxidant. This oil is formulated to meet lubrication requirements of both gasoline and diesel engine and suitable for all seasons.

**Applications:** Recommended for naturally aspirated diesel engines operating under severe conditions. Also suitable supercharged diesel engines and Vehicles encountering continuous start-stop operation, small stationary engines & pumpsets.

Pack Size 500ML, 1L, 3.5L, 5L, 20L, 210L



## AD-BLUE

### Power AdBlue (DEF) DIESEL EXHAUST FLUID

AdBlue® is a high-purity aqueous urea solution for the application as NOx reducing agent for SCR (Selective Catalytic Reduction) exhaust gas after treatment of vehicles with Diesel engine

**Benefits:**

- Reduces maintenance costs
- Extends SCR system lifespan
- Ensures SCR system efficiency
- Improves fuel economy

Pack Size 2L, 5L, 20L, 210L

## GEAR & TRANSMISSION OIL



### TITANIC GEAR FULLY-SYNTH 75W-90, GL-5

TITANIC GEAR FULLY-SYNTH 75W-90, API GL-5 is semi synthetic manual transmission fluid, specially designed for synchromesh gearboxes requiring API GL-5 Performance. It is blended with high quality base stock, carefully selected extreme pressure additive and highly stable viscosity index improver to provide unmatched gear protection.

**Applications:** TITANIC GEAR FULLY-SYNTH 75W-90, API GL-5 is a premium quality manual transmission fluid.

**Recommended Specially for use in Synchromesh Gear Box of** Maruti, Hyundai, Tata, VW, Skoda, Ford, GM, Honda and Toyota.

Pack Size 1L, 2.5L, 20L, 210L.



### TOP GEAR DX 85W-140, GL-5

**Benefits:**

- Thermal stability
- Oxidation stability
- Compatible to a variety of plastics and polymers used in transmission cases
- Spur and helical gears
- No foam
- No pitting

**Recommended for:** Transmission gear boxes of: • TATA 1613, LPT 1613, LPT 2518, LPK 2518, Prima 2528 K • Ashok Leyland 2518, 2523, 3518, 4923 • Eicher Pro 1059, 3015 • Volvo FH 16

Pack Size 1L, 5L, 210L.



### TOP GEAR TX 80W-90, GL -5 / REAR AXEL OIL

**Benefits:**

- Thermal stability
- Oxidation stability
- Compatible to a variety of plastics and polymers used in transmission cases
- Spur and helical gears
- No foam
- No pitting

**Recommended for:**

Transmission gear boxes of: • TATA 1613, LPT 1613, LPT 2518, LPK 2518, Prima 2528 K • Ashok Leyland 2518, 2523, 3518, 4923 • Eicher Pro 1059, 3015 • Volvo FH 16

Pack Size 1L, 2.5L, 5L, 20L, 50L, 210L.



### TOP GEAR GT EP -140 GL-4

**Applications:**

Lubrication of axles and mechanical transmission systems of cars, buses, trucks and tractors which require moderate duty monograde GL-4 type of gear oils.

**Features & Benefits:**

- Anti-foaming with enhanced ability to form lubricating film.
- High oxidation stability.
- Compatible with other gear oils.
- Reduce unwanted sounds.

**Recommended For:** All types of Rotavator, Automotive and Industrial Gear Boxes

Pack Size 1L, 3L, 5L, 20L, 50L, 210L.



### TOP GEAR GX EP-90, GL-4

**Applications:** Lubrication of axles and mechanical transmission systems of cars, buses, trucks and tractors which require moderate duty monograde GL-4 type of gear oils.

**Features & Benefits:**

- Anti-foaming with enhanced ability to form lubricating film.
- High oxidation stability. • Compatible with other gear oils.
- Reduce unwanted sounds.

**Recommended For :** All types car, buses, truck, tractor & Suitable for Automotive and industrial gear boxes.

Pack Size 500ML, 1L, 5L, 10L, 20L, 26L, 50L, 210L.



### POWER ATF-TQ

**Application:**

- Recommended for Automatic transmission and power steering systems of automobiles and earth moving machinery.
- Provides excellent frictional performance.
- Superior anti wear protection.
- Excellent oxidation resistance.
- Seal compatibility.

Pack Size 500ML, 1L, 5L, 15L, 20L, 50L, 210L.



### SPECIAL UTTO / OIB SAE-30

**Applications:** Special Wet Brake Oil designed with special additives to keep Tractor's Wet Brake cool & noise free; it works as a Hydraulic fluid for lifting mechanism operation, has excellent gear protection properties and is thus 3 in 1 oil.

**UTTO Meets OEM Level Performance:** API GL-4(SF 3I), John Deere J20C/J20D, J.I. Case MS 1205/1206/1207/1209/1210, Massey Ferguson CMS M1135/41/43/45-Ford M2C 86B/C, 134D-Case New Holland MAT 3505, 3525/3526

**UTTO Plus Meets OEM Level Performance:** API-GL4, Mahindra Tractors equipped with Wet disc brakes providing

**Meets Viscosity Specification Grade:** SAE - 30

**UTTO Recommended For:** New Holland, Force, John Deere, Massey Ferguson, Ford, J.I Case, Swaraj, TAFE, Escorts, Eicher

**UTTO Plus Recommended For:** Mahindra & Mahindra, Sonalika

Pack Size 1L, 5L, 10L, 20L, 26L, 50L, 210L



### RPO OIL 1000

Suitable for use in Heavy Industrial Gear boxes, Farming Roaters, Borewell Hammer Oil, Road Rollers, Old Bullet Gear box & in manufacture automobile rubber tyres, belting, battery case etc. Where colour is not an important parameter.

**Product Description:** RPO 1000 is aromatic type of rubber process oil with good solvency. The oil is dark in colour and has good solvency. It is compatible with most rubber polymer.

**Benefits:** • Adequate miscibility • Excellent plasticizing properties

Pack Size 500ML, 1L, 5L, 10L, 20L, 26L, 50L, 205L

## GREASE



### EPL-2 GREASE

EPL-2 Grease is an extreme pressure Lithium soap grease that contains oxidation, rust and corrosion inhibitors and provides excellent EP properties.

**APPLICATIONS:** EPL-2 Grease is recommended for lubrication of plain and rolling element bearings in normal through heavy-duty industrial applications. It is suitable where loads are high or shock loads are present. It resists water washing and provides rust protection for bearings if water is present. The softer grades are particularly suitable for use in centralized lubrication system and can be used for both automotive and industrial applications.

Pack Size 5KG, 18KG, 180KG



### LONG LIFE GEL GREASE

NLGI - 3 Grease of Lithium, is able to deliver service life of 75 000 km in long haul trucks.

**Recommended for:**

- Anti friction ball and roller bearings of all automotive wheel applications in trucks, tractors, cars, 3W, 2W

**Benefits:**

- Corrosion & water resistant
- Maintains oil film on friction areas at all operating temperatures

Pack Size 500GM, 1KG, 3KG, 5KG, 18KG, 180KG



### AP-3 GREASE

NLGI - 3 Grease of Lithium, is able to deliver service life of 40 000 km in long haul trucks.

**Recommended for:**

- Anti friction ball and roller bearings of all automotive wheel applications in trucks, tractors, cars, 3W, 2W

**Benefits:**

- Corrosion & water resistant
- Maintains oil film on friction areas at all operating temperatures

Pack Size 500GM, 1KG, 5KG, 18KG, 180KG



### AP-3 CRUSHER GREASE

NLGI-3 of Lithium based grease with high water and oxidation resistance properties.

**Recommended For** Crusher Heavy Big Size Bearings.

**Benefits**

- Excellent anti-corrosion and anti-rust characteristics.
- Resistance of High water and oxidation
- Excellent structural stability.
- Withstand high operating temperatures.

Pack Size 5KG, 18KG, 180KG




### GOLD MP-3 GREASE (CALCIUM)

**Product Description:** GOLD MP-3 Grease is a Calcium based water resistant multipurpose tacky Gel Grease.

**Application:** Recommended for general application for plain and anti-friction bearing where temperatures are moderate below 70°C. This grease is also recommended for chassis lubrication including suspension and steering system and for certain open and semi enclosed gears as well as chain drives of farm equipments.

Pack Size 500GM, 1KG, 5KG, 18KG, 180KG.

## INDUSTRIAL HYDRAULIC & GEAR OIL



### HYDRO POWER AW-46 / 32

**Applications:**

- Recommended for wide variety of Industrial Hydraulic and Circulation systems
- In high and low pressure Mobile Hydraulic systems
- Mobile construction equipment
- Hydraulic control systems of machine tools and presses
- Hydraulic vane, piston and gear type pumps

**Benefits:**

- Long service life
- Excellent anti-wear, anti-rust and anti-corrosion properties
- Good oxidation stability
- Excellent antifoam and air release characteristics

**Pack Size** AW-46: 5L, 26L, 50L, 210L • AW-32: 26L, 50L, 210L



### HYDRO POWER AW-68

**Applications:**

- Recommended for wide variety of Industrial Hydraulic and Circulation systems
- In high and low pressure Mobile Hydraulic systems
- Mobile construction equipment
- Hydraulic control systems of machine tools and presses
- Hydraulic vane, piston and gear type pumps

**Benefits:**

- Long service life
- Excellent anti-wear, anti-rust and anti-corrosion properties
- Good oxidation stability
- Excellent antifoam and air release characteristics

**Pack Size** 1L, 5L, 26L, 50L, 210L.



### HYDRO POWER AW-100

**Applications:**

- Recommended for wide variety of Industrial Hydraulic and Circulation systems
- In high and low pressure Mobile Hydraulic systems
- Mobile construction equipment
- Hydraulic control systems of machine tools and presses
- Hydraulic vane, piston and gear type pumps

**Benefits:**

- Long service life
- Excellent anti-wear, anti-rust and anti-corrosion properties
- Good oxidation stability
- Excellent antifoam and air release characteristics

**Pack Size** 20L, 210L.



### PREMIUM 10W

**Applications:**

PREMIUM 10W Hydraulic Transmission Oil is blended from high refined base stocks incorporating carefully selected detergent, dispersant and anti-oxidant additives to give the desired performance.

**Performance Level :** API CF

**Product Features**

- Powershift Transmissions
- Final drives
- Oil immersed brakes
- Hydraulic systems

**Pack Size** 20L, 210L.



### GEAR EP-150

**Application:** GEAR OIL EP 150 is a sulphur-phosphorus based industrial gear oil; formulated from extra refined base oils, has exceptional oxidation resistance and is able to meet important industry performance specifications. It is recommended for use in cement mill kiln gear boxes, ball mill gear boxes, steel roll mill gear drives and in non-gear applications like plain bearings and shaft couplings.

**Meets requirements of :**

- AGMA 9005 - E02 (EP) • US Steel 224

**Pack Size** 20L, 210L.



### GEAR EP -220

**Application:** GEAR OIL EP 220 is a sulphur-phosphorus based industrial gear oil; formulated from extra refined base oils, has exceptional oxidation resistance and is able to meet important industry performance specifications. It is recommended for use in cement mill kiln gear boxes, ball mill gear boxes, steel roll mill gear drives and in non-gear applications like plain bearings and shaft couplings.

**Meets requirements of :**

- AGMA 9005 - E02 (EP) • US Steel 224

**Pack Size** 5L, 20L, 50L, 210L.



### GEAR EP -320

**Application:** GEAR OIL EP 320 is a sulphur-phosphorus based industrial gear oil; formulated from extra refined base oils, has exceptional oxidation resistance and is able to meet important industry performance specifications. It is recommended for use in cement mill kiln gear boxes, ball mill gear boxes, steel roll mill gear drives and in non-gear applications like plain bearings and shaft couplings.

**Meets requirements of :**

- AGMA 9005 - E02 (EP) • US Steel 224

**Pack Size** 5L, 20L, 210L.



### GEAR EP -460

**Application:** GEAR OIL EP 460 is a sulphur-phosphorus based industrial gear oil; formulated from extra refined base oils, has exceptional oxidation resistance and is able to meet important industry performance specifications. It is recommended for use in cement mill kiln gear boxes, ball mill gear boxes, steel roll mill gear drives and in non-gear applications like plain bearings and shaft couplings.

**Meets requirements of :**

- AGMA 9005 - E02 (EP) • US Steel 224

**Pack Size** 20L, 210L.



### COMPRESSOR OIL 100

**APPLICATIONS:** Recommended for cylinder lubrication of single and multistage air compressors with moist air and provide excellent lubrication of piston rings, valves, cylinder liners etc.

**FEATURES & BENEFITS**

- Formulated with selected base stocks and providing satisfactory lubrication under prolonged high temperature and load conditions
- Excellent resistance to washing effect of water
- These are further fortified with anti-rust and anti-corrosion agent and have good fluidity at low temperature.

**PERFORMANCE LEVEL:** Meets the requirement of DIN 51506 VD-L group specifications for air compressor oil

**Pack Size** 20L, 210L.



### REFRIGERATION OIL

**APPLICATIONS**

- It is recommended for wide range of refrigeration compressors, both reciprocating as well as rotary, using ammonia and carbon dioxide
- It is not recommended for R-12, R-22 and other Freon Refrigerants

**FEATURES & BENEFITS**

- The oil blended from specially selected deep hydro finished lube base stocks
- This oil to provide low pour point, dryness good chemical stability & ready solubility in liquefied refrigerants

**Pack Size** 20L, 210L.



## About us...

**Amberol Lubtech Pvt. Ltd.** a leading organization involved in marketing & manufacturing under **Amberol Lubtech Pvt. Ltd** of automotive, industrial lubricants & fluids for OEMs Lubricant organizations.

**Amberol Lubtech Pvt. Ltd.** has been able to rise and make a mark for itself because of our belief in the cardinal and key rationale of customer care and tending to the minutest of details. **Amberol Lubtech Pvt. Ltd** is driven by the demand from the Indian & export consumers.

Top organization West Coast Lubricants & Asphalts Pvt. Ltd. Is Ultra Group of Companies following stringent quality standards that have been approved by esteemed clients / multinationals like Valvoline, Cummins Ltd. Shell India Markets Pvt. Ltd., Castrol India Ltd., GS Caltex India Pvt. Ltd., Gulf Oil Corporation & Total Elf Fina Pvt. Ltd., was also manufacturing for our brand Amberol Lubtech Pvt. Ltd. for automotive and industrial products etc.

Our plant has facilities to blend all types of lube oils (viz. Engine oils, Gear oils, Transmission oils, Industrial oils etc.), Super clean oils & specialty products (Coolants, Brake fluids & DEF Fluids), Viscosity Modifiers etc. catering about 700 SKU's for different clients.

## Our Mission

The vision of **Amberol Lubtech Pvt. Ltd.** Is to introduce and serve primary and secondary consumers in the automotive lubricants replacement market with high quality products coupled with diligent customer service and timely delivery at down-to-earth prices. We take it to be our privilege to be able to reach out to the consumers with the best quality Lube Oils at low costs yet without cutting corners

- We aim to provide consumers the very best quality Lubes for new Generation vehicles.
- **Amberol Lubtech Pvt. Ltd.** is committed to protect the environment and will introduce specific products to assist in a direct and an indirect manner towards fuel efficiency of components and vehicles.
- Serving top quality products and timely delivery gives us the confidence to support marketing partners in developing a sustainable supply, commercial success and brand presence.
- Not only remain responsive to our customers' needs but also how much they can derive from us.
- Constant innovation and meticulous work, allows us to retain customers in the long run.

25 years of presence in lubricants industry, gives us the confidence to support marketing partners in developing a sustainable supply, commercial success and brand presence.

### Amberol Lubtech Pvt. Ltd. Product Portfolio:-

#### Automotive Lubricants

- Petrol Engine Oils
- Diesel Engine Oils
- 2 & 3 Wheeler Oils
- Tractor Engine Oils & UTTO
- Gas / CNG Engine Oils
- Gear Oils
- Automotive Greases

#### Industrial Lubricants

- Hydraulic Oils
- Cutting Oils (Neat & Soluble)
- Heat Transfer Oils
- Industrial Gear Oils
- Quenching Oils
- Rust Preventive Oils
- Transmission Oils (CAT Specs)

#### Fluids

- Coolant
- DEF / AdBlue

#### Specialty Lubricants

- Fully/Semi Synthetic Engine Oil





**Amberol<sup>+</sup>**  
LUBRICANTS

MARKETED & MANUFACTURED BY :  
**AMBEROL LUBTECH PRIVATE LIMITED**  
REGD. OFFICE: SILVER SPRINGS, A-621,  
PLOT NO. 6, TALOJA MIDC, OPP. DENA BANK,  
TALOJA, NAVI MUMBAI - 410 208, MAHARASHTRA.  
MOBILE +91 788 780 7676  
TELEPHONE NO. 1800 210 1366 (TOLL FREE)  
E-MAIL: mail@amberolplus.com  
[www.amberolplus.com](http://www.amberolplus.com)

Authorised Distributor / Dealer Name and Address